

SPECIFICATIONS

Push Button Presto Shower Valve 102mm (Fixed Time&Temp)

Concealed self-closing tap

GENERAL INFORMATION

Valve Type: Self Closing Metering Valve Valve Activation: Manual Push Button Valve Installation Type: Concealed Wall Mount Body Material: Lead Free Solid Brass Finish Type: Chrome Plated Finish

CONNECTIONS & DIMENSIONS

Connection Inlet: 3/4" MPT (3/4" MPT Adapters included) Connection Outlet: 3/4" MPT (3/4" MPT Adapters included)

Escutcheon Plate Diameter: 5.1" (130mm)

Valve Body Length: 4" (102mm)

PRODUCT FEATURES

Time Adjustable: No, 30 Seconds Temperature Adjustable: No

Working Temperature Range: 40 Degrees F - 170 Degrees F

Built-in Premix: No

Lead Free and Corrosion Resistant

Vandal Resistant: reduces tampering and risk of flooding

Water Saving Up To 85%!

WHAT'S INCLUDED

Push Button Shower Valve

Rosette Plate (5 in Diameter)


Rough-In

Filter Screen (3/4 in)

Paper Washer (3/4 in)

Adapters With Washers (3/4 in FPT x 3/4 in MPT)







40-170 °F



1-5.5 bar



10 l/min (3 bar)



3/4" MPT



EN 12540, EN 1982, EN 12164, EN 12165, ISO 9227 ADA COMPLIANT ASME A112.18.1 CSA B125.1



15 Year Warranty

KING SUPPLY COMPANY 16 WHITINS RD SUTTON, MA 01590 1 (866) 352-6652 INFO@KINGSUPPLY.COM

38212