



SPECIFICATIONS

3/4" Hose Bibb Vacuum Breaker - Self-Draining
Frost Proof Self-Draining Hose Bibb Vacuum Breaker | Lead-Free, Solid Brass

GENERAL INFORMATION

Valve Type: Hose Bibb Vacuum Breaker
Turn Style: Quarter Turn
Body Material: Lead Free Solid Brass

CONNECTIONS & DIMENSIONS

Connection Inlet: 3/4" FHT
Connection Outlet: 3/4" MHT
Height: 2" (50mm)
Depth: 1.3" (34mm)

PRODUCT FEATURES

Max Working Temperature: 180 Degrees F
Working Temperature Range: 33 Degrees F - 180 Degrees F
Lead Free and Corrosion Resistant
Vandal Resistant: Tamper-Proof thread locking device
1 built in check valve

WHAT'S INCLUDED

Hose Bibb Vacuum Breaker



MATERIAL SPECIFICATION

NO.	PARTS	BRASS REGULAR	BRASS NO LEAD
1	PACKING	RUBBER (NBR) SN-719F	RUBBER (NBR) SN-719F
2	BOLT	BRASS (C37700)	BRASS (C37700)
3	HOSE BONNET	STAINLESS STEEL (304)	STAINLESS STEEL (304)
4	PACKING	POM M90 FORMOCON FM090 CF500P	POM M90 FORMOCON FM090 CF500P
5	PACKING	RUBBER (NBR) SN-719F	RUBBER (NBR) SN-719F
6	MIDDLE BODY	BRASS (C37700)	BRASS (C46400)
7	WASHER	BRASS (C26000)	BRASS (C26000)
8	PACKING	RUBBER (NBR) SN-719F	RUBBER (NBR) SN-719F
9	SPRING SEAT	POM M90 FORMOCON FM090 CF500P	POM M90 FORMOCON FM090 CF500P
10	SPRING	STAINLESS STEEL (304)	STAINLESS STEEL (304)
11	HOSE BODY	BRASS (C37700)	BRASS (C46400)
CERTIFIED UNDER		C UPC, ASSE	AB 1953



33-180 °F



Low Lead AB 1953



1 Check Valve



3/4" FHT



C UPC Approved
CSA B64.2 Approved
ASSE 1011 Certified



1 Year Warranty