

SPECIFICATIONS

3/4" Hose Bibb Vacuum Breaker - Piston Activated, Self-Draining
Frost Proof Self-Draining Hose Bibb Vacuum Breaker | Lead-Free, Solid Brass

GENERAL INFORMATION

Valve Type: Hose Bibb Vacuum Breaker
Turn Style: Quarter Turn
Body Material: Lead Free Solid Brass

CONNECTIONS & DIMENSIONS

Connection Inlet: 3/4" FHT
Connection Outlet: 3/4" MHT
Height: 2" (50mm)
Depth: 1.4" (35mm)

PRODUCT FEATURES

Max Working Temperature: 180 Degrees F
Working Temperature Range: 33 Degrees F - 180 Degrees F
Lead Free and Corrosion Resistant
Vandal Resistant: Tamper-Proof thread locking device
1 built in check valve

WHAT'S INCLUDED

Hose Bibb Vacuum Breaker



MATERIAL SPECIFICATION

NO.	PARTS	BRASS REGULAR	BRASS NO LEAD
1	PACKING	RUBBER (NBR) SN-719F	RUBBER (NBR) SN-719F
2	BOLT	BRASS (C37700) STAINLESS STEEL (304)	BRASS (C37700) STAINLESS STEEL (304)
3	HOSE BONNET	BRASS (C37700)	BRASS (C46400)
4	PACKING	RUBBER (NBR) SN-719F	RUBBER (NBR) SN-719F
5	HOSE BODY	BRASS (C37700)	BRASS (C46400)
6	SPRING	STAINLESS STEEL (304)	STAINLESS STEEL (304)
7	SNAP RING	POM M90 FORMOCON FM090 CF500P	POM M90 FORMOCON FM090 CF500P
8	PACKING	RUBBER (NBR) SN-719F	RUBBER (NBR) SN-719F
9	SPRING SEAT	POM M90 FORMOCON FM090 CF500P	POM M90 FORMOCON FM090 CF500P
10	SPRING	STAINLESS STEEL (304)	STAINLESS STEEL (304)
11	KNOB	POM M90 FORMOCON FM090 CF500P	POM M90 FORMOCON FM090 CF500P
CERTIFIED UNDER		C UPC, ASSE	AB 1953



33-180 °F



3/4" FHT



Low Lead AB 1953



C UPC Approved
CSA B64.2 Approved
ASSE 1011 Certified



1 Check Valve



1 Year Warranty